



(1) Publication number:

0 370 591 A3

(12)

EUROPEAN PATENT APPLICATION

21) Application number: 89250092.7

② Date of filing: 20.11.89

(5) Int. Cl.⁵: **E21B 23/00**, E21B 23/04, E21B 29/02, E21B 17/10

(3) Priority: 23.11.88 US 275265

② Date of publication of application: 30.05.90 Bulletin 90/22

Designated Contracting States:
BE DE FR GB NL

Date of deferred publication of the search report: 14.08.91 Bulletin 91/33

(7) Applicant: Terrell, Jamie B.


1916 Christopher Drive Everman Texas 76140(US)

Inventor: Terrell, Jamie B. 1916 Christopher Drive Everman Texas 76140(US)

Representative: UEXKÜLL & STOLBERG Patentanwälte Beselerstrasse 4 W-2000 Hamburg 52(DE)

(4) Downhole chemical cutting tool.

(5) A downhole chemical cutting tool having an anchoring system employing interchangeable slip arrays (38) of progressively larger outside diameters that can be used economically to adjust the range of the anchoring system. The range can be further adjusted by utilizing interchangeable slip expansion mandrels (44). This anchoring system both anchors and centralizes the chemical cutting tool. The cutting tool includes a slip shaft (32) that provides fluid communication between the propellant section (24) and chemical section (26), thence to the slip piston (36) that receives the interchangeable slip arrays (38). The slip shaft and slip piston are threadedly connected to a set coiled tension spring (34). Interchangeable slip expansion mandrels (44) connected to the slip shaft (32) below the slip arrays are constructed with ball bearings (44a) on the surface that receives the slip arrays expanding the slip segments into a gripping engagement an usually large angle as the slip piston is actuated by the application of fluid pressure during the cutting operation. The interchangeable slips are configured so that th gripping teeth (38k,j,i,h) will simultaneously engag the internal surface (110) of the wellbore pipe being cut. During the cutting operation th application of fluid pressure activates the slip assembly and discharges th chemical cutting fluid from the chemical section into the fluid jet section of the tool at high temperature and velocity. After the release of fluid pressure the slip assembly reliably releases the tool due to the large angle of engagement of the slip segments.





EUROPEAN SEARCH REPORT

Application Number

EP 89 25 0092

	Ottobles of desired with	Indication where accordate	D-4	avant .	C ASSIGNATION OF THE
ategory	Citation of document with indication, where appropriate, of relevant passages			evant claim	E 21 B 23/00 E 21 B 23/04 E 21 B 29/02
A,D	US-A-4 620 591 (TERRELL) * Abstract; figure 10 *		1,5,	8,18	
A,D	US-A-4 415 029 (PRATT) * Abstract; fig. *		1,5,	8,18	E 21 B 17/10
A,D	US-A-4 619 318 (TERRELL * Abstract; fig. *		1,5,	8,18	
A,D	US-A-4 345 646 (TERRELL *Abstract; fig. *	-) 	1,5,	8,18	
A,D	US-A-4 125 161 (CHAMMA * Abstract; fig. *	AS)	1,5,	8,18	
A	DE-A-1 911 900 (LONGYE SUPPLIERS) * Fig. *	AR DIAMOND CORE DRII	_L 1,5,	8,18	
Α	US-A-4 637 471 (SODERB Abstract; fig. "	ERG)	1,5	8,18	TECHNICAL FIELDS SEARCHED (Int. CL5)
					E 21 B
		·			
	The present search report has I	been drawn up for all claims			
	Place of search	Date of completion of s	earch	-	Examiner
	The Hague	17 May 91			WEIAND T.
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same catagory A: technological background			E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons		
O: P:	non-written disclosure intermediate document theory or principle underlying the ir	wention	&: member of document		e patent family, corresponding